

Product data sheet

Specifications



Switch Socket - 15A 250V - 3 phase 3 pole - flat pin - IP66 (grey)

S56C315RPGY

Main

Range	WPS
Product or component type	Switch and socket-outlet
Colour tint	Light grey

Complementary

Material	PVC (polyvinyl chloride) UV stabilised
Surface finish	Gloss
Width	101 mm
Height	203 mm
Rated current	15 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Network number of phases	3 phases
Number of gangs	2 gangs
Pin number	3
Device composition	Flat pin
Number of poles	3
Mounting mode	Surface mounted

Environment

IP degree of protection	IP66
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.8 cm
Package 1 Width	10.1 cm
Package 1 Length	20.2 cm
Package 1 Weight	750 g
Unit Type of Package 2	CAR

Number of Units in Package 2	12
Package 2 Height	22.1 cm
Package 2 Width	36 cm
Package 2 Length	44.5 cm
Package 2 Weight	9000 g
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	130 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	198000 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)