Product datasheet

Specifications



Ultimate Screwless flat plate unswitched fused connection stainless steel BI

GU5400-BSS

| *** |
|-----|
| |

| Aesthetic name | Screwless flat plate |
|---------------------------|-----------------------------|
| Product or component type | Unswitched fused connection |
| Switch function | |
| Colour tint | Steel Black |

Complementary

| Pilot light | without neon indicator |
|-------------------------|------------------------|
| Number of gangs | 1 gang |
| Material | Steel |
| Mounting support | Wall mounted |
| Fixing mode | By screws |
| Rated current | 13 A at 230 V AC |
| Connections - terminals | Screw terminals |
| Quantity per set | Set of 1 |
| Height | 88 mm |
| Width | 88 mm |
| Depth | 23 mm |

Environment

| IP degree of protection | IP20 |
|-------------------------|---------|
| Standards | BS 1363 |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|---------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.8 cm |
| Package 1 Width | 8.8 cm |
| Package 1 Length | 2.3 cm |
| Package 1 Weight | 0.001 g |

Offer Sustainability

| EU RoHS Directive | Compliant EU RoHS Declaration |
|----------------------------|--|
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes |

Recommended replacement(s)