

Easy9 miniature circuit breaker- 3P - 16 A - C curve - 6000 A - 400 V

EZ9F56316

viain	۱
-------	---

Range	Easy9
Device application	Distribution
Product or component type	Miniature circuit-breaker
Device short name	Easy9 MCB
Poles	3P
Number of protected poles	3
[In] rated current	16 A
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	С
Breaking capacity	10000 A Icn at 220 V AC 50/60 Hz conforming to IEC 60898-1 6000 A Icn at 400 V AC 50/60 Hz conforming to IEC 60898-1
Suitability for isolation	Yes conforming to IEC 60898-1

Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	220 V AC 50/60 Hz 400 V AC 50/60 Hz
Magnetic tripping limit	510 x ln
[lcs] rated service breaking capacity	6 kA 100 % x Icn at 400 V AC 50/60 Hz conforming to IEC 60898-1
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60898-1
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60898-1
Contact position indicator	Yes
Control type	Toggle
Local signalling	Without
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	81 mm

Width	54 mm
 Depth	66.5 mm
Colour	Grey (RAL 7035)
Mechanical durability	10000 cycles
Electrical durability	4000 cycles
Connections - terminals	Tunnel type terminal (top or bottom) 125 mm² rigid Tunnel type terminal (top or bottom) 116 mm² flexible
Tightening torque	2 N.m top or bottom
Environment	
Standards	IEC 60898-1
Product certifications	CE VDE
IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	2
Tropicalisation	2
Relative humidity	95 % at -560 °C
Ambient air temperature for operation	-560 °C
Ambient air temperature for storage	-4085 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	5.3 cm
Package 1 Length	8.5 cm
Package 1 Weight	326 g
Unit Type of Package 2	BB2
Number of Units in Package 2	4
Package 2 Height	8.5 cm
Package 2 Width	9 cm
Package 2 Length	22 cm
	1000
Package 2 Weight	1326 g
Package 2 Weight Offer Sustainability	1326 g
	Green Premium product
Offer Sustainability	
Offer Sustainability Sustainable offer status	Green Premium product
Offer Sustainability Sustainable offer status REACh Regulation	Green Premium product REACh Declaration Compliant
Offer Sustainability Sustainable offer status REACh Regulation EU RoHS Directive	Green Premium product REACh Declaration Compliant EU RoHS Declaration

Product Environmental Profile

Yes

RoHS exemption information

Environmental Disclosure

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)