# **Product datasheet**

Specifications





## Vivace 45A 250V Twingang Vertical Double Pole Switch with Neon, Aluminium Silver

KBT31VDR45N\_AS

***

Range	Vivace
Product or component type	Switch
Device short name	KBT31
Device application	Control
Switch function	Double 1-way vertical

#### Complementary

Complementary	
Device presentation	Complete mechanism
Actuator	Rocker
Pilot light	Neon indicator lamp
Number of gangs	2 gangs
Colour tint	Wine gold
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	120.6 mm
Embedding depth	47 mm
Rated current	45 A at 250 V AC, inductive 45 A at 250 V AC, resistive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	pillar terminal
Tightening torque	0.4 N.m
Clamping connection capacity	16 mm²
Width	86 mm
Height	146 mm

### **Environment**

Standards	SS 227 MS IEC 60669-1
Ambient air temperature for operation	-540 °C
Relative humidity	095 %
Environmental characteristic	Indoor use

## **Packing Units**

PCE
1
8.6 cm
3.4 cm
14.6 cm
179.9 g
BB1
5
9.5 cm
15 cm
19 cm
970 g
CAR
50
21 cm
31.5 cm
50 cm
9246 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

### Recommended replacement(s)