

Product datasheet

Specifications



Ultimate Screwless dimmer switch 250W/VA, 2gang, 2way, main & LV, st. steel

GU6422CSS

Main

Range of product	Ultimate
Range	Ultimate
Aesthetic name	Screwless flat plate
Product or component type	Dimmer
Device application	Control
Load type	Incandescent lamp 230 V AC halogen lamp: 250 W
Colour tint	Stainless steel
Quantity per set	Set of 1

Complementary

Switch function	2-way
Device mounting	Wall mounted
Dimmer application	Resistive load Inductive load
[Ue] rated operational voltage	230 V AC 50 Hz
Number of gangs	2 gangs
Connections - terminals	Screwless terminals
Fixing mode	By screws M3.5 x 25 mm By screws M3.5 x 30 mm
Height	88 mm
Width	88 mm
Depth	25 mm

Environment

Standards	BS EN 60669-2-1
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	5.500 cm
Package 1 Width	9.600 cm
Package 1 Length	9.500 cm
Package 1 Weight	297.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Height	21.000 cm
Package 2 Width	30.000 cm
Package 2 Length	50.000 cm
Package 2 Weight	15.280 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	1600
Package 3 Height	100.500 cm
Package 3 Width	120.000 cm
Package 3 Length	100.000 cm
Package 3 Weight	508.960 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)