AvatarOn, rotary dimmer, 250 VA, Wine Gold

E8331RD250_WG

Main

Product or component type	Dimmer
Device presentation	Complete product
Provided equipment	Screws
Dimmer application	Capacitive load Inductive load Ohmic load
Dimmer control	Rotary push type
Load type	Incandescent lamps - 50250 W - 220240 V AC High voltage halogen lamp - 50250 W - 220240 V AC Electronic transformer - 50250 VA Dimmable LED - 50250 VA
Colour tint	Wine gold
Type of packing	Carton
Quantity per set	Set of 8
Market segment	Residential Small commercial

Complementary

[Ue] rated operational voltage	220240 V AC 50/60 Hz
Protection type	Surge arrester Thermal fuse
Actuator	Knob
Fixing mode	By screws
Clamping connection capacity	<= 2 x 2.5 mm² for flexible cable(s) <= 2 x 2.5 mm² for rigid cable(s)
Wire stripping length	12 mm
Material	Polycarbonate: plastic part Brass: terminals Steel coated with zinc chromate: terminal screw
Device mounting	Flush
Height	86 mm
Width	86 mm
Embedding depth	35 mm

_							٠
Fr	W	ro	n	m	ρ	n	t

IP degree of protection	IP20
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	060 °C
Relative humidity	1095 %
Environmental characteristic	Oil and vapour resistant
Standards	IEC 60669-2-1 CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.63 cm
Package 1 Width	8.8 cm
Package 1 Length	8.8 cm
Package 1 Weight	125.6 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	19 cm
Package 2 Length	19.5 cm
Package 2 Weight	1.105 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	48
Package 3 Height	21 cm
Package 3 Width	30 cm
Package 3 Length	39.5 cm
Package 3 Weight	7128.8 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Recommended replacement(s)