Product datasheet

Specifications



20A 250V 1 Gang Double Pole Switch with Neon and Earth

KB31D20NE

| Range | Vivace |
|-------------------------------|-----------------------------|
| Product or component type | Switch |
| Device short name | KB31 |
| Device application | Control switch |
| Additional switch application | On/off switching |
| Number of rocker | 1 |
| Switch function | Double 1-way with earth |
| Colour tint | Surround: white Base: white |

Complementary

| Technology type | Electromechanical |
|--------------------------------|---|
| Device presentation | Complete product |
| Actuator | Rocker |
| Pilot light | Neon indicator lamp |
| Number of gangs | 1 gang |
| Colour tint | White |
| Material | Polycarbonate: grid plate Polycarbonate: surround Nylon: base |
| Surface finish | Glossy |
| Surface treatment | Untreated |
| [Ue] rated operational voltage | 220250 V |
| Type of packing | Plastic bag |
| Network type | AC |
| Quantity per set | 1 |
| Sale per indivisible quantity | 1 |
| Rated current | 20 A |
| Projecting depth | 8 mm |
| Device mounting | Flush |
| Mounting support | Wall mounted |

| Operating altitude | 02000 m |
|---------------------------------------|--|
| Relative humidity | 095 % |
| Ambient air temperature for operation | -540 °C |
| Standards | SS 227 IEC 60669-1 MS IEC 60669-1 |
| Environment | |
| Depth | 32 mm |
| Height | 86 mm |
| Width | 86 mm |
| Wire stripping length | 12 mm |
| Clamping connection capacity | <= 4 mm² for rigid or stranded cable(s) 4 mm² |
| Tightening torque | 0.4 N.m |
| Terminal identifier | L2 N2 L1 N1 |
| Connections - terminals | 8 screw terminals |
| Contacts material | Brass and phosphor bronze |
| Network frequency | 50/60 Hz |
| | 20 A at 250 V AC, resistive 250 V AC |
| Number of terminals | 20 A at 250 V AC, inductive |
| Embedding depth Number of terminals | 8 |
| Connections - terminals | Screw terminal 20 mm |
| Fixing center | 60.3 mm |
| | |

Packing Units

Environmental characteristic

IP degree of protection

Indoor use

IP20

| Unit Type of Package 1 | PCE |
|------------------------------|-----------|
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 122.125 g |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|--------------------------|-------------------------------|
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration |

Pro-active China RoHS declaration (out of China RoHS legal scope)

| RoHS exemption information | Yes |
|----------------------------|-------------------------------|
| Environmental Disclosure | Product Environmental Profile |
| Contractual warranty | |
| Warrantv | 18 months |

Recommended replacement(s)