

Product datasheet

Specifications



20A-16AX 250V 2 Gang 1 Way Switch

E8232L1F20

Main

Range	Pieno
Product or component type	Switch
Device application	Control
Load type	Fluorescent Resistive

Complementary

Device mounting	Surface Flush
Wiring device mounting	Surface Flush
Switch function	1-way
Rated current	20 A at 250 V AC 50 Hz
Local signalling	Fluorescent (white)
Number of gangs	2 gangs
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s)
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	23 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %

Standards	BS EN 60669-1 MS IEC 60669-1 SS 227-1 IEC 60669-1 GB 16915.1
-----------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.7 cm
Package 1 Width	8.7 cm
Package 1 Length	2.3 cm
Package 1 Weight	0.001 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)