

# Product datasheet

Specifications



## 20A-16AX 250V 2 Gang 1 Way Switch with Fluorescent Locator, Matt Black

E8232L1F20\_MB\_G1

### Main

Range	Pieno
Product or component type	Switch
Device application	Control
Load type	Fluorescent Resistive
Cover frame colour tint	Matt black

### Complementary

Device mounting	Surface Flush
Wiring device mounting	Surface Flush
Switch function	1-way
Rated current	20 A at 250 V AC 50 Hz
Local signalling	Fluorescent (white)
Number of gangs	2 gangs
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm <sup>2</sup> for stranded cable(s) 2 x 2.5 mm <sup>2</sup> for solid cable(s)
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	23 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	BS EN 60669-1 MS IEC 60669-1 SS 227-1 IEC 60669-1 GB 16915.1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.55 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	120.79 g
Unit Type of Package 2	CAR
Number of Units in Package 2	80
Package 2 Height	21 cm
Package 2 Width	32.5 cm
Package 2 Length	50 cm
Package 2 Weight	9663.2 g
Unit Type of Package 3	PAL
Number of Units in Package 3	1600
Package 3 Height	84 cm
Package 3 Width	82.5 cm
Package 3 Length	100 cm
Package 3 Weight	210264 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------

## Recommended replacement(s)