# **Product datasheet**

Specifications



# Lisse - Fuse connection unit - LED - 1 gang - 13 A - white moulded

GGBL5011

via	un
-----	----

Range	Lisse
Aesthetic name	White moulded
Product or component type	Fuse connection unit
Device presentation	Complete product
Colour tint	white moulded
Quantity per set	Set of 10

#### Complementary

Pilot light	LED
Actuator	Rocker
Number of gangs	1 gang
Material	Urea (carbamide)
Device mounting	Wall mounted
Fixing mode	By screws
Rated current	13 A at 250 V AC
Connections - terminals	Screw terminals
Type of packing	Carton
Width	87 mm
Height	87 mm
Depth	28 mm
Net weight	0.105 kg

#### **Environment**

Standards	BS 1363
IP degree of protection	IP20

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.000 cm

Package 1 Width	9.000 cm
Package 1 Length	9.000 cm
Package 1 Weight	105.700 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.500 cm
Package 2 Width	15.500 cm
Package 2 Length	18.500 cm
Package 2 Weight	1.144 kg
Unit Type of Package 3	S04
Number of Units in Package 3	100
Package 3 Height	30.000 cm
Package 3 Width	40.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	11.925 kg

# Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

# Recommended replacement(s)