



Vivace 13A 250V TwinGang Switched Socket, Aluminium Silver

KB25_AS

Main

Range	Vivace
Product or component type	Switched socket
Device short name	KB25
Device application	Power supply Power supply
Device presentation	Complete product
Switch application	On/off switching
Main colour tint	Aluminium silver
Colour tint	Aluminium silver

Complementary	
Outlet poles configuration	2P + E
Number of gangs	2 gangs
	Aluminium silver
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	120.6 mm
Embedding depth	22.0 mm
Rated current	13 A at 250 V AC, resistive
Network frequency	50/60 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	N L Earth
Tightening torque	0.4 N.m
Clamping connection capacity	2 x 4 mm²

2	v	2	5	m	m^2

Width	147 mm
Height	87 mm
Depth	35 mm

Environment

Standards	SS 145 BS 1362-2 MS 589
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-560 °C
Relative humidity	095 %
Operating altitude	<= 2000 m
Environmental characteristic	Indoor use
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.1 cm
Package 1 Width	8.6 cm
Package 1 Length	14.6 cm
Package 1 Weight	148 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	812 g
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	21 cm
Package 3 Width	31.5 cm
Package 3 Length	50 cm
Package 3 Weight	7730 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration

Pro-active China RoHS declaration (out of China RoHS legal scope)

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Contractual warranty	
Warranty	18 months

Recommended replacement(s)