Product datasheet

Specifications



13A 250V 1Gang switched socket

E8215

Main

Range	Pieno
Product or component type	Power socket-outlet
Device application	Power supply
Switch function	Switch
Rated current	13 A at 250 V AC 50 Hz
Number of gangs	1 gang
Load type	No inductive load

Complementary

Wiring device mounting	Flush Surface
Outlet poles configuration	2P + E china
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Switch: pillar terminals Socket: clamp terminal
Clamping connection capacity	2 x 2.5 mm² for solid cable(s)
Width	87 mm
Height	87 mm
Depth	8.8 mm

Environment

Ambient air temperature for operation	-540 °C
Relative humidity	095 %
Standards	GB 16915.1-2003 GB 2099.1-2008

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.7 cm

Package 1 Width	8.7 cm
Package 1 Length	0.88 cm
Package 1 Weight	0.001 g

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)