

Product datasheet

Specifications



Pieno - 10A 250V - 4 gang 1 way switch with fluorescent locator

E8234L1F

Main

Range of product	Pieno
Product or component type	Switch
Switch function	1-way
Switch application	Switch
Rated current	10 AX at 250 V AC 50 Hz
Local signalling	Fluorescent (white)
Number of gangs	4 gangs
Load type	Fluorescent Resistive

Complementary

Wiring device mounting	Surface Flush
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s)
Width	87 mm
Height	87 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	GB 16915.1 IEC 60669-1
Product certifications	CCC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.414 cm

Package 1 Width	8.712 cm
Package 1 Length	8.709 cm
Package 1 Weight	102.6 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.699 cm
Package 2 Width	18.957 cm
Package 2 Length	19.121 cm
Package 2 Weight	1.118 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Height	22.21 cm
Package 3 Width	30.565 cm
Package 3 Length	39.9 cm
Package 3 Weight	7.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)