

Product datasheet

Specifications



Vivace 10A 250V 1G BellPress Switch with marking

KB31BPB/B

! Discontinued on: 20 June 2023

! Discontinued

Main

Range	Vivace
Product or component type	Bell press switch
Device short name	KB31
Device application	Control
Additional switch application	Bell switch
Switch function	1-way

Complementary

Device presentation	Complete mechanism
Marking	With symbols
Actuator	Rocker
Number of gangs	1 gang
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Type of packing	Blister
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	10 A at 250 V AC, inductive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	pillar terminal
Terminal identifier	L1 COM

L2

Tightening torque	0.4 N.m
Clamping connection capacity	1.5 mm ²
Width	87 mm
Height	87 mm

Environment

Standards	IEC 60669-1 SS 227 MS IEC 60669-1
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

Recommended replacement(s)