

CAT. N° 8 322 37



FUSED CONNECT UNIT SYNERGY -DOUBLE POLE SWITCH+LED+CORD -13 A-250 V~ SLEEK DESIGN POLISHED STAINLESS STEEL

Pack (number of units)	1
Volume (dm³)	0,462
Weight (g)	173,00

Product characteristics

Fused connection units switched 13 A - 250 V~

- Conform to BS 1363: Part. 4
- Front cable outlet with cord grip
- Fuses supplied
- Locked captive fuse carrier (padlockable)
- \blacksquare For flush-mounting, back box to be min. 35 mm deep
- \blacksquare Supplied with 1 gang side extension (3 mm thick) in case of extra wiring space needed
- Nominal plate dimensions: 86 x 86 mm

DP switched - with blue LED power indicator + cord outlet

■ Polished stainless steel

General characteristics

Synergy $^{\text{TM}}$ - cooker control units, fused connection units and cable outlets - Sleek Design

- Sleek design
- BSS: Plates made of austenitic Stainless Steel non-magnetic grade 304 L
- PSS: Plates made of Stainless Steel + rust resistance
- GG: Plates made of Stainless Steel + rust resistance
- Terminal screws captive and backed off ready for cabling large angled terminal entries
- Compact mechanism for maximum wiring space

Documentation

- Catalogue pages & additional information
 - Description page (p.593)
- Agreements & certificates of conformity
 - ASTA-880



^{*} All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis: before-tax price list, May 2018