

CAT. N° 8 323 51



## ROTARY UNIVERSAL DIMMER SYNERGY -1 GANG -2-WAY PUSH SLEEK DESIGN POLISHED STAINLESS STEEL

Pack (number of units)	1
Volume (dm <sup>3</sup> )	0,677
Weight (g)	217,00

### Product characteristics

#### Push on/off rotary universal dimmers 5 W / 300 W 100 - 240 V~ - 50/60 Hz

##### 1 gang - 2-way push switches

- Conform to IEC 60669-2-1
- For flush-mounting back box to be min. 40 mm deep
- Equipped with overvoltage and short-circuit protection
- Screw terminals
- For all types of lamps:
  - dimmable LEDs: 5 W to 75 W
  - dimmable compact fluorescent lamps: 5 W to 75 W
  - halogen with ferromagnetic or electronic transformer: 5 VA to 300 VA
  - fluorescent tube - ballast: 5 VA to 300 VA
  - halogen and incandescent 230 V: 5 W to 300 W
- When switched on, gradually (2 seconds) lights up at the level set before last switch-off
- Nominal plate dimensions: 86 x 86 mm
- Polished stainless steel

### General characteristics

#### Synergy™ - single pole switches and dimmers - Sleek Design

- Sleek design
- BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L
- PSS: Plates made of Stainless Steel + rust resistance
- GG: Plates made of Stainless Steel + rust resistance
- Terminal screws captive and backed off ready for cabling - large angled terminal entries
- Compact mechanism for maximum wiring space

### Documentation



#### Catalogue pages & additional information

- [Description page \(p.590\)](#)



#### Installation & technical data

- [F02305EN-00](#)



#### Installation instructions & related documents

- [LE08934AA\\_EN-AR](#)



#### Agreements & certificates of conformity

- [OC / CB-210106146GZU-VOC001](#)
- [OC / CB-SE-104104](#)
- [OC / CB-SE-104454](#)
- [OC / CB-SE-105791](#)
- [OC / CB-SE-105791M1](#)
- [OC / CB-SE-105791M2](#)